



ECO GREENBOARD

Datasheet

Quality Covers eco greenboard is a covering material for the dry construction job. The board has a light water repellent coating and is therefore excellent for protecting floors in dry indoor areas.

Material composition

New material board from 1st class Scandinavian wood fibers. The material has a mineral coating, which has light water-repellent properties.

Specifications

Dimensions	Dimensions Various weights and sizes available
Coating	No LDPE coating
Packaging	On europallets
Color	Brown and/or white
Usability	Processing properties are not time-dependent
Storage	Dry and protected from humidity

Area of application

Quality Covers eco greenboard provides protection for the short, dry construction job, indoors.

Properties

- Slightly water repellent
- Consistent quality



ECO GREENBOARD

Datasheet

Processing

- Make the substrate dry, clean and dust-free
- Switch off underfloor heating
- Lay the eco greenboard flat on the subfloor
- Overlap by 10cm and seal the material with a suitable tape
- Always test beforehand whether the product is suitable for the substrate

Notes

Quality Covers eco greenboard is not suitable for newly laid floors that still have to breathe or harden, in which case we recommend Quality Covers Breath fleece.

Eco greenboard is not resistant to aggressive substances, the substrate must be permanently dry, clean, dust-free and free of solvents. If the eco greenboard is damaged (e.g. by reuse) it must be replaced.

Our application recommendations are to support the buyer or processor and are based on our testing and experience. You are responsible for checking the suitability for the intended purpose, for example by testing on a small area. The manufacturer assumes no liability for any damage that may occur. No rights can be derived from this data sheet. Kwabo Techniek B.V. reserves the right to make technical changes and developments.